MURR ELEKTRONIK
stay connected

## UNIVERSAL CONTACTOR SUPPRESSOR


RC, 230VAC/DC/20VA/W


230 V AC/DC
RC
For other configurations and voltages, please inquire.

[Link to Product]

### Illustration




Product may differ from Image

### Commercial data

| | |
|---|---|
| ECLASS-6.0 | 27371013 |
| ECLASS-6.1 | 27371013 |
| ECLASS-7.0 | 27371013 |
| ECLASS-8.0 | 27371013 |
| ECLASS-9.0 | 27371013 |
| ECLASS-10.1 | 27371013 |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-29

MURR ELEKTRONIK
stay connected

| | |
|---|---|
| ECLASS-11.1 | 27371013 |
| ECLASS-12.0 | 27371013 |
| ETIM-5.0 | EC002498 |
| customs tariff number | 85363010 |
| GTIN | 4048879020336 |
| Packaging unit | 1 |
| **Compatibility \| Compatible with** | |
| Appropriate contactors | universal |
| **Electrical data** | |
| Damping factor | 1.5× UN |
| Holding power max. | 20 W |
| **Electrical data \| Input** | |
| Input voltage AC min. | 110 V |
| Input voltage AC max. | 250 V |
| Input voltage DC min. | 110 V |
| Input voltage DC max. | 250 V |
| **Installation \| Connection** | |
| Connection information | flexible connection wires |
| **Device protection \| Media** | |
| Flame resistance | flame retardant |
| **Mechanical data \| Material data** | |
| Combustibility class housing (UL94) | V-0 |
| Material housing | Plastic |
| **Mechanical data \| Mounting data** | |
| Height | 22 mm |
| Width | 27 mm |
| Depth | 11 mm |
| **Environmental characteristics \| Climatic** | |
| Operating temperature min. | -20 °C |
| Operating temperature max. | 70 °C |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-29