MURR ELEKTRONIK
stay connected

MIRO GSM DI6 DO4R 24VDC

The product is discontinued.Last order date 12/22/2017.

Link to Product

Commercial data	
ECLASS-6.0	27242216
ECLASS-7.0	27242216
ECLASS-8.0	27242216
ECLASS-9.0	27242216
ETIM-5.0	EC000740
customs tariff number	85176200
GTIN	4048879321303
Packaging unit	1
Electrical data | Input	
Input voltage DC min.	12 V
Input voltage DC max.	48 V
Input current	15 mA
Electrical data | Output	
Switching voltage AC max.	250 V
Switching voltage DC max.	250 V
Switching current max.	10 A
Device protection	
Condition lifetime	load-dependent
Device protection | Electrical	
Degree of protection (EN IEC 60529)	IP20
Electrical lifetime	30000000 Cycles
Device protection | Mechanical	
Mechanical endurance	30000000 Cycles
Mechanical data | Material data	
Material contact	Ag Ni 90/10
Mechanical data | Mounting data	
Mounting method	screwed, geschnappt
Suitable for mounting type	mounting rail, (EN 60715)
Height	80 mm
Width	90 mm
Depth	59,5 mm
Environmental characteristics | Climatic	
Operating temperature min.	-25 °C
Operating temperature max.	55 °C
Storage temperature min.	-40 °C
Storage temperature max.	85 °C
Connection type 7	
Connection type 1	Ant
Connection type 2	Input
Connection type 3	Input Digital
Connection type 4	Output
Connection type 5	Output
Connection type 6	Prog
Connection type 7	SIM

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-29

Family construction form	SMA
Gender	female
No. of poles	2
PIN 1	Signal
PIN 2	PE
Connection	Screw terminals SK
Family construction form	terminal
Gender	female
Color contact carrier	green
No. of poles	10
PIN 1	+
PIN 2	+
PIN 3	-
PIN 4	-
PIN 5	1
PIN 6	2
PIN 7	3
PIN 8	4
PIN 9	5
PIN 10	6
Connection	Screw terminals SK
Family construction form	terminal
Gender	female
Color contact carrier	green
No. of poles	6
PIN 1	1
PIN 2	2
PIN 3	3
PIN 4	4
PIN 5	5
PIN 6	6
Connection	Screw terminals SK
Family construction form	terminal
Gender	female
Color contact carrier	green
No. of poles	12
PIN 1	1 14
PIN 2	1 12
PIN 3	1 11
PIN 4	2 24
PIN 5	2 22
PIN 6	2 21
PIN 7	3 34
PIN 8	3 32
PIN 9	3 31
PIN 10	4 44
PIN 11	4 42
PIN 12	4 41
Connection	Screw terminals SK
Family construction form	terminal
Gender	female
Color contact carrier	green
No. of poles	4
PIN 1	1

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-29

PIN 2	2
PIN 3	3
PIN 4	4
Family construction form	D-Sub
Gender	female
Color contact carrier	black
No. of poles	9
Family construction form	SIM
Gender	male
No. of poles	6

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-29