MURR ELEKTRONIK
stay connected

POTENTIAL TERMINAL BLOCK

4 x blue/brown

Potential terminal block
Multi color

[Link to Product]

Illustration



Product may differ from Image

Commercial data	
ECLASS-6.0	27141106
ECLASS-7.0	27141106
ECLASS-8.0	27141106
ECLASS-9.0	27141106
ETIM-5.0	EC001283
customs tariff number	85369010
GTIN	4048879327589
Packaging unit	1

Electrical data | Supply	
Operating voltage AC max.	30 V
Operating voltage DC max.	30 V
Total current max.	10 A

Installation	
Connection cross section max.	2,5 mm²
AWG number min.	28
AWG number max.	14

Installation | Connection	
Connection	Spring clamp plug-in terminals

Device protection | Electrical	
Degree of protection (EN IEC 60529)	IP20

Mechanical data | Mounting data	

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-29

Height	70 mm
Width	56 mm
Depth	32,5 mm
Environmental characteristics | Climatic	
Operating temperature min.	0 °C
Operating temperature max.	55 °C
Storage temperature min.	-40 °C
Storage temperature max.	85 °C

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-29

Murrelektronik GmbH | Office Park 4, 4.OG/Top A.45 | 1300 Wien-Flughafen | Fon +43 1 706 45 25-0 | Fax +43 1 706 45 25-300 | shop@murrelektronik.at | shop.murrelektronik.at