

Xelity 4TX GE Unmanaged Switch 4 Port 1000Mbit

4 port unmanaged switch  
Connection cables are in the online shop under "Connection Technology".

Link to Product

Illustration



Product may differ from Image



Electrical data | Supply

|                           |      |
|---------------------------|------|
| Operating voltage DC      | 24 V |
| Operating voltage DC min. | 9 V  |
| Operating voltage DC max. | 30 V |

Industrial communication

|                             |             |
|-----------------------------|-------------|
| Data transmission rate max. | 1000 MBit/s |
|-----------------------------|-------------|

Industrial communication | Ethernet functionality

|                              |                |
|------------------------------|----------------|
| Auto-crossover               | yes            |
| Auto-negotiation             | yes            |
| duplex                       | Full duplex    |
| Switch type                  | unmanaged      |
| VLAN unmanaged (IEEE 802.1Q) | Tag forwarding |

Diagnostics

|               |                                  |
|---------------|----------------------------------|
| Alarm contact | no                               |
| Diagnostic    | No voltage                       |
| LED display   | Ethernet connection/data traffic |

Device protection | Electrical

|                                     |      |
|-------------------------------------|------|
| Degree of protection (EN IEC 60529) | IP20 |
|-------------------------------------|------|

Mechanical data | Material data

|                  |         |
|------------------|---------|
| Color housing    | black   |
| Material housing | Plastic |

Mechanical data | Mounting data

|                 |            |
|-----------------|------------|
| Mounting method | geschnappt |
|-----------------|------------|

|                            |                                |
|----------------------------|--------------------------------|
| Suitable for mounting type | Mounting rail TH35, (EN 60715) |
| Height                     | 140 mm                         |
| Width                      | 30 mm                          |
| Depth                      | 85,1 mm                        |

#### Environmental characteristics | Climatic

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -40 °C |
| Operating temperature max. | 75 °C  |
| Storage temperature min.   | -40 °C |
| Storage temperature max.   | 85 °C  |

#### Connection type 2

|                          |                           |
|--------------------------|---------------------------|
| Connection type 1        | 4                         |
| Family construction form | RJ45                      |
| Gender                   | female                    |
| Color contact carrier    | black                     |
| No. of poles             | 8                         |
| PIN 1                    | TD +                      |
| PIN 2                    | TD -                      |
| PIN 3                    | RD +                      |
| PIN 4                    | n.c.                      |
| PIN 5                    | n.c.                      |
| PIN 6                    | RD -                      |
| PIN 7                    | n.c.                      |
| PIN 8                    | n.c.                      |
| Connection               | Spring clamp terminals FK |
| Family construction form | terminal                  |
| Gender                   | female                    |
| Color contact carrier    | green                     |
| No. of poles             | 4                         |
| PIN 1                    | 24 V DC (UB 1)            |
| PIN 2                    | 0 V                       |
| PIN 3                    | PE                        |
| PIN 4                    | n.c.                      |

#### Commercial data

|                       |               |
|-----------------------|---------------|
| customs tariff number | 85176200      |
| GTIN                  | 4065909013243 |
| Packaging unit        | 1             |