

ASSEMBLY MODULE MP 6


Mounting rail / screw-type terminal


6 pairs of solder pins screw terminals connected to solder pin pairs

Link to Product

Illustration







Product may differ from Image





Commercial data		
ECLASS-6.0	27260710	
ECLASS-6.1	27141149	
ECLASS-7.0	27141149	
ECLASS-8.0	27141149	
ECLASS-9.0	27141149	
ECLASS-10.1	27141149	
ECLASS-11.1	27141149	
ECLASS-12.0	27141149	

The information in this Product-PDF has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-04-16

Operating temperature max.



ETIM-5.0	EC000683
customs tariff number	85369010
GTIN	4048879042277
Packaging unit	1
Electrical data Supply	
Operating voltage AC	50 V
Operating voltage DC	50 V
Operating current max.	5 A
Installation	
Connection cross section max.	4 mm ²
Installation Connection	
Connection	Screw terminals SK
Connection information	Lötstützpunktpaare (Raster 5 mm)
Device protection Media	
Flame resistance	flame retardant
Mechanical data Material data	
Housing properties	open design
Material housing	Plastic
Mechanical data Mounting data	
Distance of solder pins	24 mm
Mounting method	screwed, geschnappt
Suitable for mounting type	Mounting rail TH35, G32, (EN 60715)
Height	63 mm
Width	45 mm
Depth	36 mm
Environmental characteristics Climatic	
Operating temperature min.	-20 °C

60 °C