

MODLINK MSDD SINGLE COMBI INSERT ITALY

1x RJ45 + 1x data cutout

- 1x Italy (CEI 23-16)
- 1x RJ45, 8-pole metal, CAT6A (female/female)
- 1x RJ45 cut-out

Link to Product

Illustration



Product may differ from Image



| Commercial data                          |               |
|------------------------------------------|---------------|
| ECLASS-6.0                               | 27189217      |
| ECLASS-6.1                               | 27189217      |
| ECLASS-7.0                               | 27189217      |
| ECLASS-8.0                               | 27189217      |
| ECLASS-9.0                               | 27182806      |
| ECLASS-10.1                              | 27182806      |
| ECLASS-11.1                              | 27182806      |
| ECLASS-12.0                              | 27182806      |
| ETIM-5.0                                 | EC002625      |
| customs tariff number                    | 85366990      |
| GTIN                                     | 4048879601047 |
| Packaging unit                           | 1             |
| Device protection   Electrical           |               |
| Degree of protection (EN IEC 60529)      | IP20          |
| Mechanical data   Mounting data          |               |
| Height                                   | 87,5 mm       |
| Width                                    | 50,7 mm       |
| Depth                                    | 30,7 mm       |
| Environmental characteristics   Climatic |               |
| Operating temperature min.               | -5 °C         |
| Operating temperature max.               | 50 °C         |

|                          |        |
|--------------------------|--------|
| Storage temperature min. | -10 °C |
|--------------------------|--------|

|                          |       |
|--------------------------|-------|
| Storage temperature max. | 60 °C |
|--------------------------|-------|

#### Shielding plate

|                        |                  |
|------------------------|------------------|
| Connection information | Threaded hole M4 |
|------------------------|------------------|

|                   |        |
|-------------------|--------|
| Tightening torque | 0,9 Nm |
|-------------------|--------|

#### Italy (CEI 23-16)

|                               |                   |
|-------------------------------|-------------------|
| Connection cross section max. | 4 mm <sup>2</sup> |
|-------------------------------|-------------------|

|                 |    |
|-----------------|----|
| AWG number max. | 12 |
|-----------------|----|

|                      |       |
|----------------------|-------|
| Operating voltage AC | 250 V |
|----------------------|-------|

|                   |      |
|-------------------|------|
| Operating current | 16 A |
|-------------------|------|

|            |                    |
|------------|--------------------|
| Connection | Screw terminals SK |
|------------|--------------------|

|              |        |
|--------------|--------|
| No. of poles | 2 + PE |
|--------------|--------|

|                      |   |
|----------------------|---|
| Connections per pole | 2 |
|----------------------|---|

#### RJ45

|                                       |      |
|---------------------------------------|------|
| Operating voltage AC max. (UL-listed) | 30 V |
|---------------------------------------|------|

|                                       |        |
|---------------------------------------|--------|
| Operating voltage DC max. (UL-listed) | 42,4 V |
|---------------------------------------|--------|

|                             |        |
|-----------------------------|--------|
| Current operating max. (UL) | 175 mA |
|-----------------------------|--------|

|                          |      |
|--------------------------|------|
| Family construction form | RJ45 |
|--------------------------|------|

|                       |      |
|-----------------------|------|
| Family type Back side | RJ45 |
|-----------------------|------|

|                     |       |
|---------------------|-------|
| Cable category min. | Cat6a |
|---------------------|-------|

|                    |                   |
|--------------------|-------------------|
| Looking techniques | Snap-in connector |
|--------------------|-------------------|