

MODLINK MSDD SINGLE COMBI INSERT CHINA

1x RJ45 + 1x data cutout

- 1x China (white)
- 1x RJ45, 8-pole metal, CAT6A (female/female)
- 1x RJ45 cut-out

Link to Product

Illustration



Product may differ from Image



| Commercial data                          |               |
|------------------------------------------|---------------|
| ECLASS-6.0                               | 27189217      |
| ECLASS-6.1                               | 27189217      |
| ECLASS-7.0                               | 27189217      |
| ECLASS-8.0                               | 27189217      |
| ECLASS-9.0                               | 27182806      |
| ECLASS-10.1                              | 27182806      |
| ECLASS-11.1                              | 27182806      |
| ECLASS-12.0                              | 27182806      |
| ETIM-5.0                                 | EC002625      |
| customs tariff number                    | 85366990      |
| GTIN                                     | 4048879601139 |
| Packaging unit                           | 1             |
| Device protection   Electrical           |               |
| Degree of protection (EN IEC 60529)      | IP20          |
| Mechanical data   Mounting data          |               |
| Height                                   | 87,5 mm       |
| Width                                    | 50,7 mm       |
| Depth                                    | 30,7 mm       |
| Environmental characteristics   Climatic |               |
| Operating temperature min.               | -5 °C         |
| Operating temperature max.               | 50 °C         |

|                          |        |
|--------------------------|--------|
| Storage temperature min. | -10 °C |
| Storage temperature max. | 60 °C  |

#### Shielding plate

|                        |                  |
|------------------------|------------------|
| Connection information | Threaded hole M4 |
| Tightening torque      | 0,9 Nm           |

#### China (CCC)

|                                                      |                    |
|------------------------------------------------------|--------------------|
| Connection cross-section solid max.                  | 4 mm²              |
| Connection cross-section stranded/fine-stranded max. | 4 mm²              |
| Operating voltage AC                                 | 250 V              |
| Operating current                                    | 10 A               |
| Connection                                           | Screw terminals SK |
| No. of poles                                         | 2 + PE             |
| Connections per pole                                 | 2                  |
| Protection contact present                           | yes                |

#### RJ45

|                                       |                   |
|---------------------------------------|-------------------|
| Operating voltage AC max. (UL-listed) | 30 V              |
| Operating voltage DC max. (UL-listed) | 42,4 V            |
| Current operating max. (UL)           | 175 mA            |
| Family construction form              | RJ45              |
| Family type Back side                 | RJ45              |
| Cable category min.                   | Cat6a             |
| Looking techniques                    | Snap-in connector |