

## M12 female recept. A-cod. rear

wires PP 8x0.25 2.0m


Flange female M12, 8-pole Rear mounting with multi-strand wire

## Link to Product

Illustration



>	¬ WH	
)	BN	
	GN	
	YE	
; )	GY	
; )	РК	
	BU	
,	RD	
·		



M16 x 15 M12 x 1 5

Product may differ from Image



Cable length	2 m
Side 1	
Tightening torque	0,6 Nm
Mounting method	inserted, screwed
Family construction form	M12

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-20

Murrelektronik GmbH | Office Park 4, 4.OG/Top A.45 | 1300 Wien-Flughafen | Fon +43 1 706 45 25-0 | Fax +43 1 706 45 25-300 | shop@murrelektronik.at | shop.murrelektronik.at



Thread	M12 x 1	
Coding	A	
Material	Brass	
No. of poles	8	
Degree of protection (EN IEC 60529)	IP67	
Commercial data		
ECLASS-9.0	27440103	
ECLASS-10.1	27440103	
ECLASS-11.1	27440103	
ECLASS-12.0	27440103	
customs tariff number	85444290	
GTIN	4065909060902	
Packaging unit	1	
Electrical data   Supply		
Operating voltage AC max.	30 V	
Operating voltage DC max.	30 V	
Current operating per contact max.	2 A	
Diagnostics		
Status indication LED	no	
Installation   Connection		
Mounting set	M16 x 1.5	
Width across flats	SW19	
Device protection   Electrical		
Protection NEMA	3, 4, 6P	
Additional condition protection degree	inserted, screwed	
Pollution Degree	3	
Rated surge voltage	0,8 kV	
Material group (IEC 60664-1)		
Mechanical data   Material data		
Coating locking	nickel plated	
Coating of fitting	nickel plated	
Locking material	Brass	
Material screw connection	Brass	
Mechanical data   Mounting data		
Mounting method	Schraubgewinde	
Looking techniques	Schraubgewinde	
Environmental characteristics   Climatic		
Operating temperature min.	-25 °C	
Operating temperature max.	85 °C	
Additional condition temperature range	depending on cable quality	
Important installation notes		
Note on strain relief	Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties.	
Note on bending radius	Attention: Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces.	
Approvals		
UL 50E	yes	
Installation   Cable		
Cable identification	973	
wire arrangement	white, brown, green, yellow, gray, pink, blue, red	
Material wire insulation	PUR	

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-20

Murrelektronik GmbH | Office Park 4, 4.OG/Top A.45 | 1300 Wien-Flughafen | Fon +43 1 706 45 25-0 | Fax +43 1 706 45 25-300 | shop@murrelektronik.at | shop.murrelektronik.at



Amount wires	8
Outer diameter insulation	1,25 mm
Conductor crosssection (wire)	0,25 mm²
Min. operating temperature (static)	-40 °C
Max. operating temperature (fixed)	90 °C
Operating temperature min. (dynamic)	-25 °C
Operating temperature max. (dynamic)	90 °C
Flame resistance	UL 1581 § 1090   IEC 60332-2-2   UL 1581 § 1100 FT2
chemical resistance	Good, application-related testing
Gasoline resistance	Good, application-related testing
Oil resistance	Good, application-related testing   DIN EN 60811-404
Bending radius (fixed)	10 x Outer diameter

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-20

Murrelektronik GmbH | Office Park 4, 4.OG/Top A.45 | 1300 Wien-Flughafen | Fon +43 1 706 45 25-0 | Fax +43 1 706 45 25-300 | shop@murrelektronik.at | shop.murrelektronik.at