

EXACT8, 6XM8, 4 POLE BASIC HOUSING

Without homerun-cable

6-way, 4-pole

Inline face or side mounting


Plastic housings with good resistance against chemicals and oils.


The resistance to aggressive media should be individually tested for your application. Further details on request.

Link to Product

Illustration







Product may differ from Image









Commercial data		
ECLASS-6.0	27143423	
ECLASS-6.1	27279219	
ECLASS-7.0	27279219	
ECLASS-8.0	27279219	
ECLASS-9.0	27440108	

The information in this Product-PDF has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-04



stay connected

ECLASS-10.1	27440111
ECLASS-11.1	27440111
ECLASS-12.0	27440111
ETIM-5.0	EC002585
customs tariff number	85369010
GTIN	4048879055000
Packaging unit	1
Electrical data Supply	
Operating voltage DC	24 V
Current operating per contact max.	2 A
Total current max.	8 A
Device protection Electrical	
Degree of protection (EN IEC 60529)	IP65, IP67
Environmental characteristics Climatic	
Operating temperature min.	-20 °C
Operating temperature max.	70 °C
Additional condition temperature range	depending on cable quality
Connection type 1	
Family construction form	free cable end
No. of poles	14